



TITAN TUBE

DATASHEET



Optical

Colours
Customized RGGBA
Total LED power
72W
Max. power draw
48W
Emittance (at 1m)
785Lx
TLCI
≥96
CRI
≥96
Beam Angle
180°
Pixels
16

Electrical

Battery
LG Chem Lithium-ion
Battery Lifetime
70% after 300 cycles
Battery Runtime
Up to 20 hours
Charging time (nominal)
3 Hours
Input Voltage (Charger)
90-264V 47-63Hz
Input Voltage (Light)
24V, 2A

Control

Backside display
With HSI control
Wireless Modules
865-870MHz | 902-928MHz |
2.4GHz
Range
300m | 330 Yards
DMX
Wired DMX + Wireless (CRMX
&W-DMX)

Construction

Housing
Polycarbonate, metal end caps
IP Rating
IP65
Relative humidity
0-100%
Operating Temperature
0-40 °C
32-104 °F
Weight
1.35kg
3Lbs
Dimensions
Ø42 x 1035mm
Ø1.6" x H40.7"

Accessories



Charger
FP1-CHR



Eyebolt
AX1-EBLT (2 pieces Included)



Holder
AX1-H (2 pieces included)



Stand
AX1-STD (Included)



BabyPin (3/8" & 1/4"-20 threads)
AX1-BLT



WingPlate
AX1-WP (Does not include holders)



CrossPlate
AX1-CP



PowerBox
FP1-PWB



Charging case
FP1-CHRCSE



Connection cable
FP1-PWB-CAB



SnapBox
SXF44



SnapBag for 3
SBAT42



SnapBag for 1
SBAT41



SnapGrid
SGTU14W40